

BF40A·50A 엔진 토크값

HONDA
MARINE

구분	사진	항목	나사산 지름(mm), 피치 (length)	토크값		
				N·m	kgf·m	lbf·ft
크랭크 케이스/ 실린더 블록/ 크랭크 축/ 피스톤	A	케넥팅 로드 너트	M8 x 0.75	28	2.8	20.2
	B	크랭크케이스 커버 볼트 (8 x 95 mm)	M8 x 1.25	각도법		
		크랭크케이스 커버 볼트(6 x 40 mm)	M6 x 1.0	11	1.1	8.0
실린더 헤드	C	리덕션 기어 락 너트	M22 x 1.25	92	9.2	66.5
	D	캠축 볼트 (6 x 70 mm)	M6 x 1.0	14	1.4	10.1
		캠축 볼트 (6 x 35 mm)	M6 x 1.0	12	1.2	8.7
	E, F	실린더 헤드 볼트 (10 x 85 mm)	M10 x 1.25	각도법		
플라이 휠/ 타이밍 벨트	E	실린더 헤드 볼트(8 x 40 mm)	M8 x 1.25	26	2.7	20.0
	G	타이밍 폴리 볼트	M48 x 1.5	130	13.0	94.0
	H	플라이 휠 볼트	M10 x 1.0	65	6.6	48.0
	I	펄서 로터 볼트	M10 x 1.25	57	5.7	41.2
엔진 설치	J	타이밍 벨트 텐션너 볼트	M10 x 1.25	45	4.5	32.5
		마운트 케이스 볼트 (8 x 35 mm, 8 x 55 mm)	M8 x 1.25	21	2.1	15.2
		마운트 케이스 볼트 (8 x 75 mm 플랜지 볼트)	M8 x 1.25	27	2.7	19.5

