

BF200A / BF225A 엔진토크 값

구 분	그림	항 목	나사산지름 (mm), 핏치 (length)	토크값	
				N·m	kgf·m
실린더 헤드	A	흡기록커암축볼트	M8 x 1.25	24	2.4
	B	배기록커암축볼트	M8 x 1.25	24	2.4
	C	실린더헤드볼트	M12 x 1.5	39.2 (1)	4.0 (1)
타이밍벨트	D	타이밍벨트 텐서너볼트	M10 x 1.25	39	4.0
	E	타이밍벨트구동폴리 볼트	M12 x 1.25	90	9.2
실린더 블록	F	베어링캡 볼트 (11 x 131 mm)	M11 x 1.5	29 (2)	3.0 (2)
	G	측면볼트 (10 x 60 mm)	M10 x 1.25	49	5.0
	H	측면볼트 (10 x 80 mm)	M10 x 1.25	49	5.0
	I	측면볼트 (10 x 109 mm)	M10 x 1.25	49	5.0
크랭크축	J	컨넥팅로드볼트	M8 x 0.75	20 (3)	2.0 (3)
	K	크랭크축폴리볼트	M16 x 1.5	245	25.0
프라이휠	-	플라이휠볼트	M12 x 1.0	118	12.0
	-	플라이휠보스볼트	M8 x 1.25	32	3.2
마운트케이스	L, M	10 mm 마운트케이스볼트, 10 mm 플랜지너트	M10 x 1.25	44	4.5
	L, M	12 mm 마운트케이스볼트	M12 x 1.25	64	6.5

- (1) 먼저 크랭크케이스볼트를 39.2 N·m (4.0 kgf·m) 까지 조이고 103° 만큼 더 조임.
(2) 먼저 크랭크케이스볼트를 29 N·m (3.0 kgf·m) 까지 조이고 51° 만큼 더 조임.
(3) 먼저 크랭크케이스볼트를 (2.0 kgf·m) 까지 조이고 90° 만큼 더 조임.

